


Lutze TOP-T Locknuts Metal

Metal Pg, Metric and EMC Metric



Characteristics:

- Hexagonal locknut for secure tightening of cable fittings and accessories
- Temperature range up to +200°C/+392°F

Locknut Specifications:

Material Brass, nickel plated

Part No.	Thread	Ø D mm	SW mm	H mm
Pg				
LMPG7	Pg 7	16.5	15	2.8
LMPG9	Pg 9	19.8	18	2.8
LMPG11	Pg 11	23.1	21	3
LMPG13	Pg 13.5	25.3	23	3
LMPG16	Pg 16	28.6	26	3
LMPG21	Pg 21	35.2	32	3.5
LMPG29	Pg 29	45.1	41	4.0
LMPG36	Pg 36	56.1	51	5.0
LMPG42	Pg 42	66.0	60	5.0
LMPG48	Pg 48	70.4	64	5.5

Due to tapered NPT thread, we recommend using plastic locknuts with metal NPT fittings if locknut is required.

METRIC				
Part No.	Thread	Ø D mm	SW mm	H mm
LMM12	M12x1.5	16.5	15	2.8
LMM16	M16x1.5	20.9	19	3.0
LMM20	M20x1.5	26.4	24	3.5
LMM25	M25x1.5	33	30	4.0
LMM32	M32x1.5	39.6	36	5.0
LMM40	M40x1.5	50.6	46	5.0
LMM50	M50x1.5	66	60	5.0
LMM63	M63x1.5	77	70	6.0

EMC Cutting Teeth Metric:

- For secure tightening of EMC cable fittings
- To cut through paint layers or powder coatings ensuring optimal contact
- Increased vibration resistance

EMC - CUTTING TEETH METRIC				
Part No.	Thread	Ø D mm	SW mm	H mm
600460	M12x1.5	16.5	15	4.5
600461	M16x1.5	20.9	19	4.5
600462	M20x1.5	26.4	24	5.5
600463	M25x1.5	33	30	5.5
600464	M32x1.5	39.7	36	5.5
600465	M40x1.5	50.6	46	6.0
600466	M50x1.5	66	60	6.0