

# FLEX GRIP WIRE CONNECTOR

TE Connectivity (TE)'s Flex Grip wire connector - one connector for broad range of solutions - accommodates combination of 24 - 14 AWG (0.2 - 4.00 mm<sup>2</sup>) solid and stranded wires. These push-in connectors have operating levers for fast, easy and releasable wire termination. The transparent body allows users to visually confirm the proper wire strip length and insertion for good electrical installation.



## Applications

- Lighting Commercial Building Equipment
- Indoor / Interior / Retrofit Lighting
- Home Automation Applications
- Residential wiring system

## Electrical

- Current rating: 16 A
- Voltage rating: 600 V AC/DC

## Mechanical

- Operating temperature: Max 85°C
- Wire range: 24 - 14 AWG solid and stranded  
0.2 - 4.0 mm<sup>2</sup> solid and stranded
- Stripping length: 13.0 mm

## Specifications

- Application Specification: [114-137271](#)
- Production Specification: [108-137271](#)
- UL 486C

## Materials

- Housing: PA UL94-V0 & PC UL94-V2
- Contact: Brass & Stainless Steel Spring

## Benefits



- Fast and easy termination
- Flexibility to rework the wiring or reuse the connector
- One connector for any combination of solid and stranded wires
- Visually confirm for proper strip length and wire insertion with clear housing
- Built-in test slot

# FLEX GRIP WIRE CONNECTOR

## Product Selection Information


	Description	Position	Color	Part Number
	Flex Grip Wire Connector	2	Green	<a href="#">2-2834245-1</a>
	Flex Grip Wire Connector	3	Green	<a href="#">3-2834245-1</a>
	Flex Grip Wire Connector	5	Green	<a href="#">5-2834245-1</a>

## Wire Installation Instruction




## Dimensions


2-2834245-1



3-2834245-1



5-2834245-1



te.com

© 2017 TE Connectivity. All Rights Reserved. TE, TE Connectivity, and the TE connectivity (logo) are trademarks of the TE Connectivity Ltd. family of companies. Other logos, product and Company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this brochure, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

1-1773943-1 JN 01/2018

USA: +1 (800) 522-6752  
Canada: +1 (905) 475-6222  
Mexico: +52 (0) 55-1106-0800  
Latin/S. America: +54 (0) 11-4733-2200  
Germany: +49 (0) 6251-133-1999  
UK: +44 (0) 800-267666  
France: +33 (0) 1-3420-8686  
The Netherlands: +31 (0) 73-6246-999  
China: +86 (0) 400-820-6015